

AMENDMENTS TO THE CLAIMS

Please amend the claims as follows:

1. (Three Times Amended) Adaptable device for delimiting and organizing ~~architectural spaces~~
an architectural space of the type model for study and demonstration to construct interior design
projects, fair and exhibition stall, partitioning of office or industrial spaces, comprising

- space elements of reduced scale connected to each other so as to form ~~partitioning which~~
~~adapts~~ partitionings adapted to the dimensions of the architectural space to be organized
or to be depicted, and
- decorative objects of reduced scale representing elements serving for decoration or
organization of interiors,

wherein:

- each variable-length space element comprises at least two different ~~flat parts or with~~
~~volume with~~ which are flat or three-dimensional and comprise rectilinear parts, sliding
one into the other,
- the length of each space element varies continuously and linearly under its normal
conditions of use, within the limits of its minimum and maximum length,
- each space element has at least one coupling portion, forming, with a complementary
coupling portion belonging to another space element, a disassemblable coupling
permitting the intersection of a plurality of space elements articulated around the axis
created by the coupling,

- a decorative object, of a size proportional to the dimensions of the object that it represents, is positioned variably and interchangeably on a space element by means of a magnetic link, an adhesive link, or a sliding support,
- this decorative object itself has an interchangeable design held by a decoration support,
- and the entire device is of a dimension such that it occupies at most the volume of a suitcase.

2. (Twice Amended) Device according to claim 1, wherein a space element has a dimension varying continuously in a single direction, defines a plane surface or a portion of volume partially rectilinear, and is made up of at least ~~two different parts, referred to as a male part or~~ and a female part, ~~a~~ the male part sliding into ~~a~~ the female part, ~~a~~ the male part abutting against ~~a~~ the female part when the space element is in its shortest position.

3. (Twice Amended) Device according to claim 1, wherein a space element accommodates a removable decoration ~~having the same physical properties as said space element so as to facilitate holding~~ adapted to hold a decorative object.

4. (Previously Amended) Device according to claim 2, wherein the parts of a space element are adjusted such that they retain their relative position once the length of the element is defined between the limits of its minimum and maximum position.

5. (Previously Amended) Device according to claim 2, wherein one of the parts of a space element has a blocking system such that the parts retain their relative position once the length of the space element is defined, between the limits of its minimum and maximum position, and the blocking system is put in place.
6. (Twice Amended) Device according to claim 2, wherein a part of a space element, ~~preferably the male part,~~ is graduated and the other another part of a space element, ~~preferably the female part,~~ has a reference which, associated with the scale on the first part, enables the direct reading of the length of the element.
7. (Previously Amended) Device according to claim 1, wherein an intersected coupling is composed of at least two segments each made up of two portions fitting one inside the other when they are placed facing each other by simple horizontal translation, enabling the passage between its segments of at least one intersecting coupling composed of at least one segment, itself made up of two portions fitting one inside the other, thus enabling the intersection of space elements.
8. (Previously Amended) Device according to claim 6 according to a first embodiment, wherein a pin passes through the different portions of at least one coupling segment, said pin with an overall circular cross-section has a gripping zone, said pin is introduced into the internal opening created by the coupling portions after the coupling portions are placed facing each other and that the

groups of space elements remain integral with each other and pivot relative to each other once the couplings are assembled.

9. (Previously Amended) Device according to claim 6 according to a second embodiment, wherein the coupling portions of the intersected and intersecting groups of space elements are connected by insertion of the male portions into the female portions by elastic deformation of the material of which they are made and that the groups of space elements remain integral with each other and pivot relative to each other once the couplings are assembled.

10. (Twice Amended) Device according to claim 1, wherein a space element made from a material without ferromagnetic properties acquires ~~this~~ a ferromagnetic property by mounting, on at least one part of its surface, of a thin material adapted to the shape of the space element and having ferromagnetic properties so as to accommodate a magnetized decorative object.

11. (Previously Amended) Device according to claim 1, wherein the space elements are placed on a foldable surface, having ferromagnetic properties so as to accommodate a magnetized decorative object.

12. (Previously Amended) Device according to claim 1, wherein two space elements are held in their relative positions by a removable linking accessory, in particular a square, equipped with at least two links.

13. (Three Times Amended) Device according to claim 1, wherein the decorative objects are ~~designed~~ adapted to accommodate a removable design held by a decoration support and said decorative objects are held in position on a space element by a temporary link ~~of which is~~ a magnetic link ~~type~~ or a sliding link ~~type~~.

14. (Twice Amended) Device according to claim 1, wherein certain decorative elements are obtained ~~starting from an evolute designed so as~~ from an unfolded base adapted to obtain, after folding and assembly, rigidity sufficient to permit the manipulation efforts generated by mounting on a space element with a magnetic or adhesive link present on at least one face of the decorative element, and leaving at least one placement position on at least one edge of at least one face capable of accommodating a decoration support.

15. (Twice Amended) Device according to claim 1 according to an embodiment of the device using space elements without magnetic properties, wherein certain decorative elements are obtained ~~starting from an evolute designed so as~~ from an unfolded base adapted to obtain, after folding and assembly, rigidity adequate to permit the manipulation efforts generated by mounting on a sliding link, leaving at least one placement position on at least one edge of at least one face capable of accommodating a decoration support and providing at least one recess to permit the passage of said sliding link designed to position the decoration element on a space element.

Serial Number: 09/926,203

Group Art Unit: 3712

16. (Previously Amended) Device according to claim 1, wherein a decoration support is produced in a shaped material enabling placement and holding of an interchangeable design inserted between the decoration support and the decorative object on which said decoration support is applied.